GRIDGEAR SOLUTIONS LTD
1610 DERWENT WAY #14
DELTA, BC V3M 6W1
INFO@GRIDGEAR.CA
+1.888.512.1392

GRID GEAR

FLUSH MOUNT, SINGLE CHANNEL, SOLID STATE, kWh METER FOR SUBMETERING

PRODUCT CODE: GG-FLUSH



PRODUCT BRIEF

GridGear's GG is a flexible, low cost, revenue grade meter, for the residential, commercial, and institutional market. The meter is UL listed (E489079), ANSI C12.20, 0.5 accuracy class as tested by UL, and designed to provide accurate measurement and verification of electricity consumption. Ease of installation and configuration makes the GG an ideal choice for many submetering applications including, new construction, retrofit upgrades and up to 3 element load monitoring. The meter comes equipped with a display, isolated pulse output and adaptable register output for interfacing to 3rd party pulse counters, recorders, and AMR systems.

GridGear supplies a line of UL approved solid and split core, revenue grade, current transformers that are calibrated with our line of meters to maximize system accuracy.

APPLICATIONS AND FEATURES

GridGear GG Flush Mount meters are designed with the following features and intended applications:

- ANSI C12.20, 0.5 accuracy class as tested by UL
- California State Approval (CTEP); New York State Approval
- UL certified enclosure options for installation in new construction and retrofit applications
- Custom-printed mounting cover
- Measurement and Verification
- Tenant cost allocation and billing
- Energy conservation and cost reduction
- Automatic Meter Reading
- Individually tested for 99.5% accuracy
- Self powered from voltage inputs
- Multi service configurations:
    - 120V Line to Neutral Single Phase 2 Wire
    - 120V Line to Neutral/240V Line to Line Single Phase 3 Wire
    - 120V Line to Neutral/208V Line to Line 3 Phase 4 Wire Wye
- Employs revenue grade accuracy, 100mA secondary solid and split core current transformers (CT's)
- Has an isolated pulse output for integration into 3rd party counters, recorders, and AMR systems
- Factory adjustable pulse weights from 4mWh/pulse to 1kWh/pulse
- UL listed (E489079) as an open style meter for use with different enclosures
- 10 year warranty on GridGear products when installed according to installation instructions